

## Medicinal white Oil

Shell Ondina X 432 is a highly refined, non-stabilised, aromatic-free mainly iso-paraffinic white mineral oil complying with the stringent pharmacopoeia purity requirements.

## DESIGNED TO MEET CHALLENGES

#### **Main Applications**

This type of oil can be used in pharmaceutical, food packaging, cosmetic and other applications like TPE/EPDM, where this high purity is required by legislation or important for the quality of the finished product.

#### Specifications, Approvals & Recommendations

Shell Ondina X 432 suitable for food packaging and other applications coming into contact with food meeting the requirements of EU Regulation 10/2011 (former directive: 2002/72/EC also known as "plastic directive").

# Typical Physical Characteristics

| Properties   |                        |       | Method                   | Shell Ondina X 432 |
|--|------------------------|-------|--------------------------|--------------------|
| Specifications   |                        |       | EC Regulation<br>10/2011 | Pass               |
| Colour (Saybolt)   |                        |       | ASTM D156                | +30                |
| Density  | @ 15°C                 | kg/m³ | ISO 12185                | 844                |
| Refractive Index   | @ 20°C                 |       | ASTM D1218               | 1.467              |
| Flashpoint COC   |                        | °C    | ISO 2592                 | 270                |
| Pour Point   |                        | °C    | ISO 3016                 | -24                |
| Kinematic Viscosity  | @ 20°C                 | mm²/s | ISO 3104                 | 165                |
| Kinematic Viscosity  | @ 40°C                 | mm²/s | ISO 3104                 | 59                 |
| Kinematic Viscosity  | @ 100°C                | mm²/s | ISO 3104                 | 9.0                |
| Sulphur (X-Ray)  |                        | %m/m  | ISO 14596                | <0.001             |
| Refractive Intercept (RI)                                    |                        |       | DIN 51378                | 1.0464             |
| Viscosity Gravity Constant (VGC)                             |                        |       | DIN 51378                | 0.770              |
| Noack Volatility   | (1h/250°C)             | %m/m  | ASTM D5800               | 1.6                |
| Molecular Weight   |                        | g/mol | ASTM D2502               | 525                |
| Carbon Number  | @ 5% Distill.<br>Point |       | ASTM D2887 mod           | C29                |
| Purity Requirements for EuPhar, USP                          |                        |       | Latest editions          | Pass               |
| Purity Requirements for FDA § 172.878, FDA §<br>178.3620 (a) |                        |       | Latest editions          | Pass               |

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

# Health, Safety & Environment

#### Health and Safety

Shell Ondina X 432 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from www.epc.shell.com

#### • Protect the Environment

Take used oil to an authorised collection point.

## Additional Information

#### • Advice

Advice on applications not covered here may be obtained from your Shell representative or technical help desks.