

Technical Data Sheet

Previous Name: Shell Donax TX

Shell Spirax S4 ATF HDX

Advanced Synthetic Technology Heavy Duty Automatic Transmission Fluid

Shell Spirax S4 ATF HDX is a superior quality automatic transmission fluid suitable for a wide range of heavy duty automotive transport and passenger car transmissions.

Based on synthetic technology base fluid, Spirax S4 ATF HDX is the ultimate performance automatic transmission fluid allowing extended drain intervals even under the most severe conditions.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- Synthetic base oil technology
- Excellent shift feeling
- Extremely low temperature fluidity
- Shear stability
- Wear protection
- Maximum oil drain interval potential
- High temperature oxidation stability

Main Applications



- Automotive automatic transmissions
- Automotive hydraulic systems
- Power steering
- Certain manual transmissions

Typical Physical Characteristics

Specifications, Approvals & Recommendations

- Ford : MERCON
- General Motors Allison : C-4
- ZF TE-ML : 04D 09 14B 16L 17C
- Voith : 55.6336 (ex G 1363)
- MB : 236.9
- MAN : 339 Typ Z2, 339 Typ V2
- Fulfils GM former Dexron IIIG specification.
- Volvo 97341
- For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Properties			Method	Shell Spirax S4 ATF HDX
Kinematic Viscosity	@40°C	mm²/s	ISO 3104	33.2
Kinematic Viscosity	@100°C	mm²/s	ISO 3104	7.2
Viscosity Index			ISO 2909	189
Density	@15°C	kg/m³	ISO 12185	847
Flash Point (COC)		°C	ISO 2592	152
Pour Point		°C	ISO 3016	-48

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

Health and Safety

Shell Spirax S4 ATF HDX is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from http://www.epc.shell.com/

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

Advice

Advice on applications not covered here may be obtained from your Shell representative.