

STORAGE

The installation of a storage, increase the selling power in the peak hours accumulating the compressed gas.
The storage is composed by modular units designed for installation both inside the SAFE containers and outdoor.



MAIN FEATURES:

- Cylinders capacity: 80Lt; type: single neck
- Max working pressure: 275 bar
- Manual discharge liquid drain (optional: automatic)
- N° sectors: 1, 2, 3 (+ blow-down volume if necessary)
- Shutoff valve (optional)
- Fusible plug (optional)
- Rupture disk (optional)
- Dedicated metallic enclosure (optional)

| CYLINDERS (n°) | CAPACITY (Lt) | CAPACITY (m3@250bar) | DIMENSIONS (mm) | WEIGHT (kg) |
|-------------------|------------------|-------------------------|----------------------|----------------|
| 2 | 160 | 42 | 700 x 333 x h:2050 | 295 |
| 7 | 560 | 150 | 2065 x 333 x h:2050 | 765 |
| 14 | 1120 | 300 | 2065 x 666 x h:2050 | 1530 |
| 21 | 1680 | 450 | 2065 x 1000 x h:2050 | 2295 |
| 28 | 2240 | 600 | 2065 x 1333 x h:2050 | 3060 |
| 35 | 2800 | 750 | 2065 x 1666 x h:2050 | 3825 |
| 42 | 3360 | 900 | 2065 x 2000 x h:2050 | 4590 |
| 49 | 3920 | 1050 | 2065 x 2333 x h:2050 | 5355 |